



## Ecco Spray Paint

### Description:

Ecco Economy Spray Paints are economical, all-purpose enamel paints recommended for touch-up, maintenance and general marking applications. Ecco Economy Spray Paints requires no primers and has excellent adhesion properties. It's rapid drying, smooth finish allows projects to be completed quickly with the best possible smooth finish.

- Highest coverage available
- Gloss finish • Variable pressure
- Fast drying
- Good hardening
- Excellent flexibility
- Strong adhesion
- Does not contain lead or any other heavy metals
- Easy to apply and repaint
- Good resistance to the elements
- High UV stability (refer to colour chart)

### Uses:

For use on ceramic, plaster, glass, metal, wood, and most other surfaces. Very good for Bicycles, Cabinets, Crafts, Door, Fences, Furniture, Hobbies, Mailboxes, Signs, Tools.

### Technical Properties:

Base	Synthetic alkyd
Heat Resistance	300°F (149°C)
Curing Time	Tack free 15-30 minutes, full cure 1 hour
Coverage	15 to 20 square feet
Cleaning	Solvent
Shelf Life	36 months
Packing	400ml can





### Colors:

008	gray primer	039	purple
010	red primer	045	Irish green RAL 6001
011	gloss black	048	dark green
012	flat black	053	yellow RAL 1003
016	gloss white	065	Orange
020	flat white	067	dark brown
026	aluminum	073	fire red RAL 3000
027	gold	082	Light Gray RAL 7038
028	copper	084	machine gray
029	chrome	095	Beige
030	18k gold	101	Fluorescent Yellow
031	clear	102	Fluorescent orange
035	light blue RAL 5012	103	Fluorescent Red
038	dark blue	104	Fluorescent Green

### Application Procedures:

#### PREPARATION

It is essential that the surface is clean, dry and free from dust, dirt or grease. Sand the surface well and remove dust. All surfaces should be cool prior to application. Lay paper on adjacent areas and mask areas to avoid overspray e.g. handles and trimming not to be painted. Ensure masking tape is removed before the paint dries to avoid damaging the paint film.

#### APPLICATION

Spray at room temperature (210C). Shake can well, until agitator ball rattles and continue to shake for two minutes. Shake can occasionally during use. Test and practice on a small area first. Test plastic trims and handles for adhesion on a small area first. Mask adjacent areas to protect from over-spray. Hold can 20 -30cm away from the surface and commence spraying. Maintaining a constant distance, spray in a sweeping motion moving on and off the spraying area. Apply several thin coats at 15 minute intervals.

#### CLEAN-UP

After use, invert the can and spray for a few seconds to clear the nozzle.

**Precautions:** Please refer to the appropriate material safety data sheet (MSDS) prior to using this product. **Warranty:** ECCO® will replace any material found to be defective. Because the storage, handling and application of this material is beyond our control, we can accept no liability for the results obtained. **Disclaimer:** All information on this data sheet is based on laboratory testing and is not intended for design purposes. | ECCO® makes no representations or warranties of any kind concerning this data.

