



## **ECT555 Ecco Underbody Protection Aerosol**

### Description:

Ecco Underbody Protection Aerosol is specially formulated to protect automotive underbodies from corrosion. The product dries to a firm, flexible, tack-free film has good abrasion resistance and effective sound-deadening properties. Rubberized for maximum thickness, durability and flexibility

- Seals
- Resists chipping
- Insulates

### Uses:

- Rocker panels
- Wheel wells
- Rust holes
- Automotive frames and under-bodies
- Gutters, roofs, drain systems
- Driveway cracks
- Post preserving

### Technical Properties:

Basis	Bitumen
Consistency	Tixotropic liquid
Appearance	Brown to black flim
Solid content	ca. 33%
Temperature resistance	25°C to +80°C-
Dry to touch	75 minutes ( $\pm$ 400 $\mu$ m wet)
Completely dried	. 135 minutes ( $\pm$ 400 $\mu$ m wet)
Cleaning	With solvent (fresh), Mechanical (cured)
Shelf Life	36 months
Packing	500ml can

### Application Procedors:

1. Provide adequate ventilation.
2. For best results, apply to clean, dry surfaces.
3. Tap bottom of can to loosen the ball agitator. Shake can for 2 minutes. For best results, aerosol can should be at room temperature before spraying.





4. Apply a uniform coating holding the can 10 to 12 inches from the surface to be coated.
5. Multiple coatings are effective. Allow 15 to 20 minutes between coats.  
Recommend a minimum of 2 coats.

**Precautions:** Please refer to the appropriate material safety data sheet (MSDS) prior to using this product. **Warranty:** ECCO® will replace any material found to be defective. Because the storage, handling and application of this material is beyond our control, we can accept no liability for the results obtained. **Disclaimer:** All information on this data sheet is based on laboratory testing and is not intended for design purposes. I ECCO® makes no representations or warranties of any kind concerning this data.

